


NOTES:

- 1. STORMTANK - CATCH BASIN ABUTMENT
- 2. CATCH BASIN OPENING MUST BE LOCATED BETWEEN TOP AND BOTTOM PLATENS
- 3. GEOFABRIC TO BE REMOVED FROM AREA OF CONTACT BETWEEN CATCH BASIN AND STORMTANK MODULES AND WRAPPED TO PREVENT SOIL INFILTRATION BETWEEN CATCH BASIN AND MODULES
- 4. NO INLET PIPE REQUIRED

Rev. No.	Date	Record of Changes	By	Appvd	Date
A	3/10/10	INITIAL DRAWING	AJG	FMK	3/12/10

 BRENTWOOD INDUSTRIES P.O.Box 605 610 Morgantown Road Reading, PA 19603 U.S.A. (610) 236-1100 / (610) 736-1280 (Fax) www.brentwoodprocess.com	Project Name	STORMTANK INSTALLATION	B
	Title	STORMTANK - CATCH BASIN ABUTMENT OPTION	
TOLERANCES	Drawn By	Date	
HEIGHT ±1/2"	AJG	3/10/10	
LENGTH ±1/2"	Drawing No.	Scale	
WIDTH ±1/2"	1:1	1:20	
<small>This is the property of Brentwood Industries, Inc. It may not be reproduced or used for any purpose other than those expressly authorized by Brentwood Industries. It shall be returned immediately upon request of Brentwood Industries.</small>			